Lenovo ThinkVision LT1913p Square Specifications

Product Specifications Reference (PSREF)

Name	**LT1913p Square Flat Panel Monitor**
Case color	**Business black**
Type-model	**60AAHAR1US**
Panel	TFT-LCD, In-Plane Switching (IPS), White LED backlight
Viewable image size	**19"** (**480.0mm**) diagonal
Max view area (W x H)	14.76" x 11.80" (374.8mm x 299.8mm)
Optimum resolution	**1280x1024**
Max pixel rate	205MHz (VGA), 165MHz (DVI)
Aspect ratio	5:4
Pixel pitch (mm)	0.0976 (H) x 0.2928 (V) mm
Dot/Pixel per Inch	86.8 dpi
Brightness	250 nits or cd/m^2 (typical)
Contrast ratio	1000:1 (typical)
Pixel response time	7ms (typical)
Color gamut	72%
Viewing angle at 10:1 CR	178° horizontal, 178° vertical
Stand	Tilt, swivel, pivot, and height adjustable stand
Bezel width	*Sides:* 0.69" (17.4mm); *top:* 0.69" (17.4mm); *bottom:* 0.69" (17.4mm)
Dimensions (HxWxD)	14.89" H x 16.18" W x 8.74" D; 378.3mm H x 411.0mm W x 221.9mm D
Power supply	24 watts typical, 27 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)
Weight	10.03 lb; 4.55kg
Limited warranty[4]	**3 year** (includes backlight)
Available date	August 2013
VESA-compliant[2]	VESA DDC2B/CI, EDID 1.3
Power management	ENERGY STAR® 6.0
Ergonomics	ISO 9241-307
Emission standards	FCC Class B
Environmental	TCO Displays 6.0, TCO Certified Edge 1.1, WEEE, RoHS, **EPEAT™ Gold rating**, ULE Gold
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 823x624 XGA: 1024x768, 1152x864, 1152x900 SXGA: 1280x1024
Presets / user settings	Standard presets: 20; user settings: 20

Features

- 19-inch Square IPS LED backlit panel
- Supports 1280x1024 resolution
- Support Lenovo Tiny PC via optional Lenovo bracket
- Mercury and arsenic free glass
- Low Halogen
- Recycled content in plastic material
- Microsoft® Windows® 7 certified
- Microsoft Windows 8 certified

ThinkVision LT1913p Square Monitor

Viewing adjustments	*Tilt:* 30° back, -5° forward; *lift:* 4.3" (110mm); *swivel:* +/- 45°
Rotating screen	Screen pivots 90 degrees from landscape to portrait
On screen display	On screen display with digital user controls (8 languages)
Control features	Direct access (buttons on front) for automatic image setup, input switch, and brightness
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, **HDCP-compliant**
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)
Ship group	Monitor, attached stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord

Limited Warranty

See details at **http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281**

Accessories

Kensington MicroSaver Cable Lock	73P2582
Kensington Twin Head Cable Lock	45K1620
Lenovo Security Cable Lock	57Y4303
Lenovo Easy Reach Monitor Stand	55Y9258

See details at **www.lenovo.com/support/monitoraccessories**

See all monitors at **www.lenovo.com/thinkvision**

See footnotes for important warranty information
US model announced July 30, 2013

© Lenovo
(LT1913P) August 2013